



# Affordable **Compact** Desktop Printers for Unrivalled Performance, Convenience & Versatility



Prints 4" Labels, Receipts, Wristbands and Tags

## CG4 Series

### INDUSTRY VERTICALS

- Healthcare
- Retail
- Transportation & Logistics
- Manufacturing
- Office

### APPLICATIONS

- Carton / Package Labelling
- Small Office Mailing
- Shelf-edge labelling
- Product Labelling
- Healthcare Specimen Labelling
- File Folder Labelling

### FEATURES

- Supports Input from Keypad
- 203 and 305dpi Print Resolution
- 4MB Flash Memory
- Thermal Transfer and Direct Thermal
- Multiple Codepage Support
- Multiple Printer Language-Compatible Options
- Safety Top Cover Latch

### ACCESSORIES



#### Keypad

- Graphical LCD display
- Alphanumeric and one-touch function keys
- SD card supported
- Enables stand-alone printing (eliminates need to connect to a PC)



#### Dispenser

- Simplifies separation of labels from a backing paper for immediate label application



#### Cutter

- Precisely cut individual labels and tags
- Allows continuous printing and cutting of labels and tags

#### ▶ Standalone Capability Using Keypad

- SATO Keypad allows users to Format, Store, Input & Print without connecting to PC
- Label formats can be stored, and called on at time of printing

#### ▶ Flexible Use & Compatibility With Legacy Systems

- 2 Standard Communication Interface configurations: USB and RS232C; or USB and LAN; or USB and Parallel
- Parallel port allows printer to be connected to legacy systems

#### ▶ High Quality Printing

- Suitable for printing graphics and logos, 2D barcodes or patient's photo on wristbands

#### ▶ User-Friendly Operation & Maintenance

- Intuitive label mechanism design allows media loading in 3 simple steps: Drop-Load-Go
- User-friendly maintenance
- The One-touch, tool-less print head release mechanism enables the print head to be quickly and easily replaced
- Printer Platen Roller can be replaced without the need for any tools

#### ▶ Print Labels with Date/Time Stamps Using Real-Time Clock Feature

#### ▶ Compatible

- Printer language options enables replacement of competitive printer models with minimal reprogramming of data streams

PRINTER MODEL		CG408	CG412
<b>PRINT SPECIFICATIONS</b>			
Print Method		Direct Thermal/Thermal Transfer	
Print Resolution		8 dots/mm (203dpi)	12 dots/mm (305dpi)
Max Print Speed		100mm/sec (4ips)	
Max. Print Area		(WxP): 104 x 300mm (4.09" x 11.81")	
CPU		32 Bits RISC-CPU 64MHz	
Printer Body Memory		Main Memory (Flash ROM): 4MB byte, SDRAM: 8MB byte	
<b>MEDIA SPECIFICATIONS</b>			
Sensor Type		I-Mark Sensor (Reflection type), Label Gap Sensor (Transparent type)	
Media	Label Size	Continuous	L: 7 ~ 300mm (0.28" ~ 11.81"), With backing paper: 10 ~ 303mm (0.39" ~ 11.93") W: 22 ~ 107mm (0.87" ~ 4.21"), With backing paper: 25 ~ 110mm (0.98" ~ 4.33")
		Tear-Off	L: 22 ~ 300mm (0.87" ~ 11.81"), With backing paper: 25 ~ 303mm (0.98" ~ 11.93") W: 22 ~ 107mm (0.87" ~ 4.21"), With backing paper: 25 ~ 110mm (0.98" ~ 4.33")
		<b>Label without Adhesive</b>	
	Label Thickness	Continuous	L: 10 ~ 303mm (0.39" x 11.93"), W: 25 ~ 110mm (0.98" x 4.33")
		Tear-Off	L: 25 ~ 303mm (0.98 x 11.93"), W: 25 ~ 110mm (0.98" x 4.33")
	Wind Direction	Face-in/Face-out	
	Media Roll Size	Max external diameter: 128mm (5.04"), Paper core inner diameter: 40mm (1.57")	
Ribbon Size	Length	Max 100m	
	Width	110mm +/- 0.5mm (4.33" +/- 0.002)	
	Wind Direction	Face Out	
<b>FONT/SYMBOLOGIES</b>			
Standard Fonts	Bitmap Fonts	Alphanumeric and Symbol: WB (18x30 dot), WL (28x52 dot), XU (5x9 dot), XS (17x17 dot), XM (24x24 dot), XB (48x48 dot), XL (48x48 dot), OCR-A (15x22 dot), OCR-A (22x23 dot), OCR-B (20x24 dot), OCR-B (30x36 dot)	
	Rasterized Fonts	CG Times, CG Triumvirate, CG Times Bold, CG Triumvirate Bold	
Barcode	1D Barcode	UPC-A/ UPC-E, EAN8/13, CODE39, CODE93, CODE128, GS1-128 (UCC/EAN128), CODABAR(NW-7), ITF, INDUSTRIAL 2of5, MATRIX 2of5, BOOKLAND, MSI, POSTNET, GS1 DATABAR (RSS)	
	2D Barcode	PDF417 (Ver2.4), MAXI Code (Ver3.0), QR Code, GS1 Data Matrix (ECC200)	
Composite Symbols		EAN-13 Composite (CC-A/CC-B), EAN-8 Composite (CC-A/CC-B), UPC-A Composite (CC-A/CC-B), UPC-E Composite (CC-A/CC-B), GS1-128 Composite (CC-A/CC-B/CC-C), GS1 DataBar Composite (CC-A/CC-B), GS1 DataBar Truncated Composite (CC-A/CC-B), GS1 DataBar Stacked Composite (CC-A/CC-B), GS1 DataBar Stacked Omni-Directional Composite (CC-A/CC-B), GS1 DataBar Limited Composite (CC-A/CC-B), GS1 DataBar Expanded Composite (CC-A/CC-B), GS1 DataBar Expanded Stacked Composite (CC-A/CC-B)	
Print Direction		Character & Barcode: 0°, 90°, 180°, 270°	
<b>COMMUNICATION INTERFACE</b>			
Interface		USB (B Type) + RS-232C (D-SUB 9 Pin) Model, USB (B Type) + LAN (10BASE-T/100BASE-TX Auto Switching) Model, USB (B Type) + IEEE1284 Model	
Command		SBPL	
<b>OPERATING CHARACTERISTICS</b>			
Power Requirements	AC Adaptor	Input Voltage: AC100V ~ 240V +/- 10%, Rated Input Voltage: AC100V / AC240V, Output Voltage: 19V	
Consumption Voltage		At Peak: 50W, At Waiting: 2.5W	
Environment	Operating	4 ~ 38°C / 30 ~ 80% RH (without condensing)	
	Storage	-10 ~ 60°C / 15 ~ 85% RH (without condensing)	
Dimension		(WxDxH): 179 x 238 x 173mm (7.05" x 9.37" x 6.81") Except protrusion part	
Weight		DT: 1.7kg (3.5 lbs) TT: 1.9kg (4.2 lbs)	
Options		Cutter, Dispenser, RTC, Keypad, Unwinder	
<b>MISCELLANEOUS</b>			
Regulatory Approvals		USA/CANADA: UL60950-1 (2001), CSA22.2 No. 60950-1-03, EUROPE: EN60950-1, CE CHINA: CCC (GB4943-2001)	
Antibacterial Finishing		Resin of the enclosure/control panel includes an antibacterial substance. This substance is tested according to JIS Z 2801. JIS stands for Japanese Industrial Standard; JIS Z 2801 was designed to quantitatively measure the ability of an antimicrobial surface to kill or inhibit the growth of microorganisms.	

## OUR PRESENCE IN ASIA

### HEADQUARTERS

SATO Corporation  
1-7-1 Shimomoguro, Meguro-ku,  
Tokyo 153-0064, Japan  
TEL: +81 3 6665 0600  
[www.satoworldwide.com](http://www.satoworldwide.com)

### OFFICES

**China (PRC)**  
SATO Shanghai Co. Ltd  
TEL: +86 21 3252 2777  
[www.satochina.com](http://www.satochina.com)

### India

SATO Argox India Private Limited  
TEL: +91 124 4498555  
[www.satoindia.com](http://www.satoindia.com)

### Indonesia

PT. SATO Label Solutions  
TEL: +62 21 2808 0270  
[www.satolabelsolutions.com](http://www.satolabelsolutions.com)

### Malaysia

SATO Auto-ID Malaysia Sdn. Bhd.  
TEL: +60 3 7620 8901  
[malaysia.satoworldwide.com](http://malaysia.satoworldwide.com)

### Philippines

SATO Philippines AIDC Solutions Inc.  
TEL: +63 49 544 9459  
[www.satoasiapacific.com/philippines](http://www.satoasiapacific.com/philippines)

### Singapore

SATO Asia Pacific Pte. Ltd.  
TEL: +65 6271 5300  
[www.satoasiapacific.com/singapore](http://www.satoasiapacific.com/singapore)

### Taiwan

SATO Taiwan Co., Ltd.  
TEL: +886 2 8912 1288  
[www.satoasiapacific.com](http://www.satoasiapacific.com)

### Thailand

SATO Auto-ID (Thailand) Co., Ltd  
TEL: +66 2 736 4460  
[www.satothailand.co.th](http://www.satothailand.co.th)

### Vietnam

SATO Vietnam Solutions Co. Ltd  
TEL: +84-28-3910 1350/1  
[www.satovietnam.com](http://www.satovietnam.com)

### REPRESENTATIVE OFFICE

**Korea**  
SATO Asia Pacific Pte Ltd  
Korea Representative Office  
TEL: +82 2 761 5072  
[www.satokorea.com](http://www.satokorea.com)

For more information about SATO in the region, visit [www.satoasiapacific.com](http://www.satoasiapacific.com)